

10/009385
3 Rec'd PCT/PTO 03 NOV 2001**LOCAL COMMUNICATION SYSTEM**Patent Number: ☐ WO9836533

Publication date: 1998-08-20

Inventor(s): STIRLING ANDREW JAMES (GB); PARMAR HARIVADEN AMBALAL (GB); PRENDERGAST SIMON EDWARD (GB)

Applicant(s):: STIRLING ANDREW JAMES (GB); COMM & CONTROL ELECTRONICS LTD (GB); PARMAR HARIVADEN AMBALAL (GB); PRENDERGAST SIMON EDWARD (GB)

Requested Patent: ☐ EP0960509 (WO9836533)

Application Number: WO1998GB00349 19980217

Priority Number (s): GB19970003216 19970217; GB19970004901 19970310; GB19970010908 19970527; GB19970016083 19970730; GB19970019415 19970912; GB19970021170 19971007

IPC

Classification: H04L12/43 ; H04L12/64

EC

Classification: H04L12/43, H04L12/64B, H04Q11/04S2

Equivalents: JP2001511971T

Abstract

Examples of local communication systems are disclosed, based on a ring of point-to-point links, providing for transport of fixed rate synchronous, fixed rate asynchronous data and variable rate data in a flexible format. Different segments of the ring network can carry data at different bit rates, while remaining synchronised to a common frame rate and having a common control channel structure, for compatibility with earlier systems. Parallel channels are provided, either permanently or when required, for signalling errors of source data, data validity/padding, flow control. Parallel variable width channels are defined with free content (stream or packet). Null data symbols are defined for padding on a byte-by-byte basis. The allocation of capacity among variable width channels is revised block by block, and a transition period is defined to allow for ring latency. Calculations for allocations of capacity are performed during one block for the next block, locally at each source station, according to predetermined rules. Information as to bandwidth requirements is exchanged prior to the calculation via a special connection signalling channel and message format.

Data supplied from the esp@cenet database - I2